







Multi Busbar Monocrystalline Half Cell PV Module

MIC 4MxxxH72(DH)-DGB

Mono Poly Solution


Power Output	Power Tolerance	Maximum Efficiency
535-555W	0~+5W	21.5%

-  Assembled with multi-busbar cells, reduce shading effect on the energy generation, lower risk of hot spot
-  Pass the test for weather resistance in harsh environments (salt mist, ammonia corrosion and sand)
-  Process optimization of high efficiency PERC solar cell and strict control on raw materials to ensure highly resistance against PID of PV module
-  Better mechanical loading tolerance with the test front side 5400pa and back side 2400pa.
-  Series and parallel design, reduce the series resistance RS of module, reduce the loss of internal electrical performance, and improve the power generation capacity of whole system.
-  Cutting solar cell technology, which significantly reduces string current and module damage, it is good choice for projects in high temperature areas.



Jinyuan Offers Long-term Quality Assurance

- 12 years Product Warranty
- 25 years Linear Power Output Warranty
- The attenuation of the power output in the first year $\leq 2\%$, the annual average attenuation after the first year $\leq 0.55\%$



* More details please read the guarantee letter.

Product Certification & Management Certification

- IEC61215/IEC61730
- ISO 9001:Quality Management System
- ISO 14001:Environment Management System
- ISO 45001:Occupation Health Safety Management System



Note: Read and understand the installation and safety manual before installation. The copyright belongs to MIC Optoelectronic Co., Ltd. If any change will not further notice.

MIC 4MxxxH72(DH) -DGB

Multi Busbar Monocrystalline Half Cell PV Module

Electrical performance parameters (STC)

Power Output	Pmax(W)	535	540	545	550	555
Rated Power Maximum Voltage	Vmp(V)	41.00	41.10	41.30	41.50	41.70
Rated Power Maximum Current	Imp(A)	13.07	13.13	13.19	13.25	13.31
Open Circuit Voltage	Voc(V)	49.60	49.70	49.90	50.10	50.30
Short Circuit Current	Isc(A)	13.83	13.89	13.95	14.01	14.07
Module Efficiency	(%)	20.7	20.9	21.1	21.3	21.5
Power Tolerance	(W)	0~+5W				

* STC : 1000W/m2 irradiance, 25°C module temperature, AM1.5 spectrum.

Different backside power gains (545W)

Double-sided gain	★	10%	15%	20%	25%
Power output	Pmax/W	560	627	654	681
Open Circuit Voltage	Voc/V	49.92	49.92	49.92	49.92
Short Circuit Current	Isc/A	15.35	16.04	16.74	17.44
Optimum operating voltage	Vmmp/V	41.32	41.32	41.32	41.32
Optimum operating current	Immp/V	14.51	15.17	15.83	16.49

Double-sided gain: under standard test conditions, the additional gain from the back versus the power from the front depends on the installation (structure, height, inclination, etc.) and the ground albedo

Electrical performance parameters (NMOT)

Power output	Pmax (W)	404.5	408.2	412.0	415.8	419.6
Rated Power Maximum Voltage	Vmp (V)	38.01	38.10	38.29	38.47	38.66
Rated Power Maximum Current	Imp (A)	10.65	10.70	10.75	10.80	10.85
Open Circuit Voltage	Voc (V)	47.12	47.22	47.41	47.60	47.79
Short Circuit Current	Isc (A)	11.06	11.11	11.16	11.21	11.26

* NMOT:800W/m2 irradiance, 20°C module temperature, 1m/s wind speed.

Structure Features

Solar Cell	182MONO(Half Cell)
Solar Cell Array	144 pcs(6x24)
Module Dimension	2278*1134*30mm
Weight	32.7kg
Glass & Backboard	2.0 mm (0.07 inches) highly transparent anti-reflection coating tempered glass
Back sheet	White
Frame	Anodized Aluminum Alloy
Junction Box	IP68 rated
Cable	4mm ² L=300 mm. PV cable
Diode Quantity	3
Wind Pressure/Snow Pressure	2400pa / 5400pa
Connector	MC4 Compatible

* More details please read the installation manual.

Temperature Characteristics

Solar Cells Rated Working Temperature	44±2 C
Temperature Coefficient (Isc)	+0.06%/C
Temperature Coefficient (Voc)	-0.35%/C
Temperature Coefficient (Pmax)	-0.38%/C

PACKAGING

Number of modules per pallet	36 pcs
17.5*2.8m Flatbed loading	864 pcs
13.0*2.35m Flatbed loading	720 pcs
20GP Standard container	--- pcs
40HQ Standard container	720 pcs


Maximum Ratings

Working Temperature	-40~+85 C
Maximum System Voltage	1500V DC
Maximum Fuse Rated Current	30A


Optional

Connector	<input type="checkbox"/> Original MC4
Cable length	<input type="checkbox"/> 1000mm <input type="checkbox"/> 900mm
Frame	<input type="checkbox"/> Black
Solar Module Dimension	<input type="checkbox"/> 2272x1128x6mm
Back sheet color	<input type="checkbox"/> Porcelain glaze <input type="checkbox"/> Transparency


Module Dimension




Back view



I-V curves of module under different temperature(545w)



I-V curves/P-V curves of module under different irradiation(545w)



Note: Read and understand the installation and safety manual before installation. The copyright belongs to MIC Optoelectronic Co., Ltd,