


# MIC 100W LED FLOOD LIGHT

LIGHT THE WORLD




ITEM No.: MFL-S100-C5M


## Electrical Specifications

• Led Power	100w
• IP / IK Grade	IP66 / IK08
• Paint process	C5M coating high resist saline
• Input Voltage	AC85-300V(50-60Hz), DC12/24V
• Operating Temperature	-20°C to +50°C 
• Driver Brand	Mearnwell driver
• Power Factor (PF)	>0.95
• Driver Efficiency	>92%
• Certification	CE,ROHS,TUV,FCC,ETL/DLC


## Photometric & Packing Specifications

• Led Lamp	SMD 3030 	• Guarantee	3 years
• Lumen Output	>13000LM	• CRI	>80
• Light Efficient	130lm/w	• CCT	2700k~6500k
• Life span	>50000 hours	• Material	Aluminum+Tempered glass
• symmetrical	30°, 60°, 90°	• Weight	6.07kg
• Dissymmetrical	Type1- 140°*70°, Type2- 70°*150°, Type3- 150°*80°, Type4- 50°*140°, Type5- 140°*140°	• Product size	330*403.5*61.1mm
		• Carton size	510*430*135mm, 1pcs/CTN

## Product size(unit:mm)



## Spectrum



## Key Features

The biggest feature of this floodlight is that it adopts the C5M anti-corrosion grade standard. (The test basis for the C5M anti-corrosion grade standard is ISO 12944-6:1998. This standard clarifies that in humid environments, high salinity, high chlorine concentration and many other The material should have a high level of corrosion resistance under adverse conditions such as fog) and is especially suitable for use in oceans, ship berths, ports, offshore operating platforms and other places.



Waterproof joints and exhaust valves



All accessories/screws is with 304 stainless steel material  
Customizable stainless steel nameplate