



ITEM No.: MFL-S400-3


Electrical Specifications

• Led Power	400w
• IP Grade	IP66
• Input Voltage	AC100-277V(50-60Hz)
• Operating Temperature	-40°C to +50°C
• Driver Brand	ZH driver
• Power Factor (PF)	>0.95
• Driver Efficiency	>92%
• Certification	CE,ROHS,TUV,FCC,SAA,ETL/DLC

Photometric & Packing Specifications

• Led Lamp	768pcs SMD 2835 PHILIPS	• Guarantee	4 years
• Lumen Output	>60000LM	• CRI	>80
• Light Efficient	150lm/w	• CCT	2700k~6500k
• Life span	>50000 hours	• Material	Aluminum+Tempered glass
• symmetrical	30°, 60°, 90°, 120°	• NW/GW	8.6kg / 9.1kg
• Dissymmetrical	70°*150°, 80°*155°	• Product size	515*443*62mm
		• Carton size	556*480*107mm, 1pcs/CTN


Product size(unit:mm)




Beam angle

9 different 15° / 30° / 60° / 90° / 120° / T2M / T3M / 50*120° / 30*90° beam angle for option.


Light distribution diagram




Installation




1. Install the lamp by the stand on the ground



2. Install lamp directly



3. Hang the lamp by the stand



4. The angle of the lamp is adjustable

Application

Widely used in workshop, warehouse, highway toll station, supermarket, exhibition building, gymnasium...etc...